

Don't Forget

- Note the date and replace your filter cartridges every 6 months.
- Your satisfaction is guaranteed. All Austin Springs products come with a 90-day warranty, and if for any reason you are not satisfied with your purchase, simply call us at 866-238-5855 for a full refund upon return.
- This filter system is designed and tested for use with genuine Austin Springs parts, including replacement filters and all hardware. Use of parts from other manufacturers may result in loss of contaminant reduction performance, system damage or failure. Use of parts from other manufacturers will also void your warranty. Please visit the original retail location for all replacement parts.

Thank you for choosing Austin Springs!

Austin Springs

1609 Shoal Creek #200, Austin, Texas 78701
866-238-5855 • www.AustinSprings.com
Manufactured in Facility 1

AS-SH-P_install_20130122

1. Remove the entire filter system from your shower pipe by turning the chrome swivel collar counter-clockwise. **(Figure A)**
2. Remove the shower head from the filter system.
3. Remove the lower filter cartridge by turning it counter-clockwise. **(Figure B)**
4. Unwrap the new replacement cartridge and remove the yellow label and plastic shipping cap from the top end of the cartridge.
5. After making sure that the upper housing O-ring is still in place, rub a coating of shampoo on the exposed surface of the O-ring to ensure a proper seal.
6. Install the new cartridge by turning it clockwise.
 - Tighten firmly by hand; if the filter is not tightened firmly it will leak around the seam between the upper filter housing and the cartridge.
7. Reattach the filter system to your shower pipe by turning the chrome swivel collar clockwise.
 - Make sure that the white washer is still in place inside the chrome swivel collar.
8. Before reattaching the shower head, flush and activate the filter until water runs clear.
 - Use cold water for the initial flushing.
 - Wait 30 seconds for temperature change.
 - Run water until clear and then turn off and back on several times.
 - Repeat this procedure until the initial surge of water is clear.

Note: do not remove the filter cartridge while the filter is still attached to the shower pipe, this may cause damage to the filter where it connects to the shower pipe, or to the pipe connection behind the shower wall.

The initial surge of water will be discolored with carbon fines and may soil your shower stall. This carbonized water is beneficial to plants and the environment. It can be discarded in a plant bed or down the drain.

AustinSprings™
Clear. Refreshing. Pure.



Replacement Instructions

Premium Shower Filter

Model: AS-SH-P-R

Figure A



Figure B

